E/MOS GROUP



EMS-5000W WOOD MEASURING MACHINE



The EMS5000W Wood is specially designed to measure the length, width, angles and linearity of your sheets.




The EMS5000 Coordinate Measuring Machines are built to give you the fastest, most accurate and high quality measurements.



EMS5000 has many technological products, software and high quality workmanship.





TECHNICAL ADVANTAGES

- Operator friendly technical design,
- Easily place the workpiece on the table thanks to the 15 degree inclined table surface,
- Thanks to the workpiece resting points on the table, it provides practical parallel positioning of your sheets,
- Y axis servo motor provides ergonomic ease of use with up and down speed control,
- The laser pointer allows youto position the camera quickly,
- With a 5 megapixel LED illuminated color camera, you can measure without any mistakes
- Thanks to the ground aluminum table, you can increase the accuracy of your nuve sheet measurements,
- With the linear guideways with roller, the axis movements provide high parallelism and precision,
- User friendly program software,



DIJITAL MEASURING SYSTEM ADVANTAGES

EMOS5000 Lcd Digital Indicators are designed for maximum precision and high performance. It provides easy operation by adding value to your metal processing machines. EMOS5000 Multifunctional digital displays and magnetic and optical linear encoders. Emos, magnetic linear rulers are designed for highrepeatability, maximum precision.

TECHNICIAL SPECIFICATIONS

- 8'' LCD Color Display
- Aluminum Outer Body
- 3-4 Axis Reading System
- 2D Measurement System
- Linear AND Angular Hole Drilling Function
- 1000 Program Memory
- Maximum Efficiency and High Performance

Performance



Digital Measuring System



EMOS DIGITAL ADVANTAGES


- Proven quality in digital mesuring systems.
- Reliable and precise magnetic measuring technology.

• IP67 protection class. They are not affected by oil, water and dirt.

- Since they are not optical glass rules, they do not scratch and break.
- They do not require cleaning and maintenance.
- Shock and vibration resistant.

• You can safely use in the most demanding and heavy workshop conditions.





INDUSTRIAL CAMERA ADVANTAGES

The Dino - Lite AD7013MTL has a 5 megapixel sensor for crystal clear images, even under higher magnification. Because of the very high resolution, the AD7013MTL is the ideal solution for displaying microscopic images on large screens or using the microscopic images for printing.

DETAILS		COMPATIBILITY			
Dino-Lite range:	Dino-Lite Long Working Distance	Interface:	USB	2.0	
LIGHTING		Operating system:	Wind	dows XP, Vista, 7, 8 & 10, MacOS 1	0.9 and up
		Included software:	Ding	Capture 2.0 (Windows), DinoXcop	pe (Mac OS)
Light/ LED type:	White	Supported image formats (Windows): BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX			
Number of LEDs:	8	Supported video formats (Windows): WMV, FLV, SWF			
LED on/off switchable:	Yes				
Infrared filter:	IR cut-filter >650 nm	FEATURES		SENSOR	
OPTICS		Special feature:	No	Sensor type:	CMOS
Magnification:	20-90×	Measurement	Yes	Resolution:	5 Megapixel (2592×1944)
Macro zoom:	No	Calibration:	Yes	Maximum frame rate:	30 Fps
Working distance:	Long	Microtouch sensor:	Yes		
Lens type:	Glass with anti-reflection coating	ESD safe:	Yes		



TECHNICAL DATA

Machine Working Size X Axis	5000 mm			
Machine Working Size Y Axis	1000 mm			
Body Material	Aluminium			
Body Color	Gray and Anthracite Gray			
Plate - Table Material	Grinded Aluminum			
Plate - Table Thickness	30 mm			
Table Angle	15°			
X Axis Linear Scale	Magnetic Linear Encoder – 0,005 micron – IP67 Protection Class Line Driver TTL 5Vdc - Length Accuracy ±0,005 mm			
Y Axis Linear Scale	Optic Scale – 0,001 micron – IP55 Protection class Line Driver TTL 5Vdc - Length Accuracy ±0,002 mm			
Digital Redout	Three Axis - 8" Lcd - Color Display Multifunctional - 2D Measurement – Aluminium Body – Power: 220Vac			
Industrial PC	10.1" With LED Backlight - Resolution: 1280 x 800 @ 60Hz - touch screen Panel Material: Aluminium - CPU: Intel® Bay Trail-D J1900 (2.00GHz - Quad core) Harddisk: 120Gb SSD - Memory: 4Gb 1333Mhz DDR3 Ram Bios: 64Mb SPI Flash ROM Storage: 1* M.2 connector (2242/2260/2280) 1* 2.5" SATA bay			
Y Axis Feed Control	2-Way Joystick			
Y Axis Control	0,4 Kw Servo Motor / Driver			
PLC	Analog Input PLC			
Y Axis Feed Speed Control	5 Kohm Infinite Turn Potentiometer			
Laser Type And Color	Point - Red			
Laser Power – Voltage - Input	1 mW – 5Vdc – 220 Vac			
Linear Guideway System	Schneeberger 25 mm - Linear Guideway: MRS 25 N and Roller Car: MRW 25 D G2 V3			
Software Language	English			
Machine Approx Weight	1500 Kg			
Machine Dimensions (mm)	Length 6000 mm - Width 1500 mm Height 950 mm			




MEASURING MACHINE USAGE

NUVE SHEET MEASUREMENT OPERATION:

- 1. The operator will lift the Nuve Sheet on the machine table.
- 2. We rest our sheet metal on the gauge pins on the table. The important point here is to check that there are no objects between the sheet and the pins. Measurement is very important for accuracy.




3. The laser on the control panel will turn on. Used for faster positioning.





4. We bring our X axis to the edge of the workpiece.With the camera crosshair on the computer, we reset the workpiece from the edge.By pressing the X0 key in our digital display, we reset the values on our w axis.





- We move the X axis again and move it to the other edge of the workpiece.
 We use the laser again for fast movement.
 With the camera crosshair we measure accurately.
- 6. We repeat the same operations within the Y axis.



SHIPPING

The machines you order are prepared by taking all precautions for shipment.

It is shipped in wooden crate for safe transportation.



