



PL310

Applications

- Valve controls
- Joysticks / Master switches

Features

- Small dimensions
- Synchro flange
- Sintered bronze bearing
- Design flexibility
- 5 Mio. cycles
- Excellent linearity, up to $\pm 0.25\%$
- Very good resolution better $0,1^\circ$

Options

- Resistance tolerance $\pm 10\%$
- Independent linearity $\pm 0.25\%$
- Custom electrical angles and switch functions available
- Mechanical end stops
- Protection class IP65
- Custom shaft design
- Custom housing design
- Ball bearings

Electrical Data

Nominal resistance	1/5/10	kOhm
Resistance tolerance	± 20	%
Independent linearity	± 1	% of meas. range
Electrical angle	340	$^\circ$
Repeatability	max. 0.1	$^\circ$
Temperature coefficient of the voltage divider	50	ppm/ $^\circ\text{C}$
Recommended wiper current	max. 1	μA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40 $^\circ\text{C}$
Min. life (electrical)	10 Mio.	cycles

Mechanical Data

Mechanical range	360	$^\circ$ (continuous)
Torque (IP54)	max. 0.7	Ncm
Min. life (mechanical)	5 Mio.	cycles
Max. permitted axial shaft load	1	N
Max. permitted radial shaft load	1	N
Operating temperature	-25 ... +85	$^\circ\text{C}$
Storage temperature	-40 ... +105	$^\circ\text{C}$
Protection class	IP54	

Standards

Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	50	g

Errors and omissions excepted.
Subject to change without notice.
State: 15-Nov-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC